



Rubcoat texture - Polyester fabric

RUBCOAT

SPECIAL COATINGS

Polyester for strengthening flexible joints and suchlike.

Product properties

Rubcoat polyester fabric is used in places where there are tensions resulting from expansion or shrinkage.

Technical data

Basis	: 100% polyester
Weight	: 45 gr/m ²
Thickness	: 0,27 mm
Stretch	: 106,6 N/5cm
Elasticity	: 42,3 %
Tensile strength	: 42,4 N

Applications

Rubcoat polyester fabric is easy to apply as an inlay in Rubcoat Coating.

How to apply

Rubcoat polyester fabric is applied to the surface pre-treated with Rubcoat coating with a brush or roller until the fabric is no longer visible.

Supply

Rubcoat polyester fabric is supplied in 100 metre rolls with standard 10 cm, 15 cm en 100 cm

Transport data

Transport via:	
road	- ADR free
sea	- IMDG free
air	- ICAO/IATA-DRG free
UN-nr	- not applicable

Remarks

We draw your attention to the fact that this information sheet cancels all previous information about this product. We retain the right to make changes in the event of technical progress.



RUBCOAT® is a trademark of Rubcoat B.V.

Correspondence address: P.O. Box 2086, 6020 AB Budel (NL) • Visitor's address: 't Inne 32c, 6021 DA Budel (NL)
Tel. : +31 495 49 19 16 • Fax : +31 495 49 37 50 • info@rubcoat.com • www.rubcoat.com

